

# **BIBS75012, Single Sided Twelve Conductor Clear Insulated Multi-Tap** Connector

By Burndy Catalog # BIBS75012

MULTI-PORT Single-Sided Entry.



#### **Features**

- Clear Plastisol covered AL6061-T6 aluminum body saves times and lowers installation costs and eliminates taping
- Clear plastisol allows visual confirmation that conductor is properly inserted
- Oxide inhibitor pre-installed inhibits moisture and contaminants from entering the contact area
- Range-taking capability reduces number of connectors necessary to carry in inventory

BIBS75012

#### General

Catalog Number

Connector Type Multi Tap Hex Key 3/8 Insulation Insulation Type Plastisol Material Aluminum Number Of Ports Physical Attribute - Number of Screws Physical Attribute - Screw Type Allen Plated Plating Type Unplated Temperature Rating 194 UNITAP™ Trade Name UPC 781810233115 7818102331155 UPC 12 Digit

### **Dimensions**

Dimension - Height inch	3.00 in
Dimension - L Length Overall	416 mm
mm	
Dimension - Length Overall	16.38 in
inch	
Dimension - Width inch	2.70 in
Dimension - Width mm	69 mm

### **Electrical Ratings**

600 V Operating Voltage Voltage - Maximum 600 V

# **Conductor Related**

Conductor - AL Str Size Range 2 AWG - 750 kcmil 2 AWG - 750 kcmil Conductor - Copper Str Size Range 2 AWG-750 KCMIL Conductor Size • AL C Str-Size Conductor Type CU C Str-Size

## **Certifications And Compliance**

Certification - CSA Approved No Certification - ETL Certification - UL Listed Direct Nο Certification - UL Recognized No Certification - cULus UL 486A-486B Industry Standard(s) Standards - Industry Standards UL 486A-486B Standards - RoHS Compliance CMStatus **UL** Listed No

#### Logistics

Minimum Pack Quantity 5

# **Product Assets**

Catalogs - UNITAP™ Products Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog Catalogs - BURNDY Master Catalog - Section A - Mechanical Customer Notices - Prop 65 Notice Interactive Catalog - BURNDY Full-Line Digital Catalog Product Cross Section Image(s) - BUR BIBS Lineart Sales Drawings - sc210991-15 Specifications - BIBS75012

