

BIBS75014, Single Sided Fourteen Conductor Clear Insulated Multi-Tap Connector

By Burndy Catalog # BIBS75014

MULTI-PORT Single-Sided Entry.



- Clear Plastisol covered AL6061-T6 aluminum body saves times and lowers installation costs and eliminates taping
- Clear plastisol allows visual confirmation that conductor is properly inserted
- Oxide inhibitor pre-installed inhibits moisture and contaminants from entering the contact area
- Range-taking capability reduces number of connectors necessary to carry in inventory

General

Catalog Number BIBS75014 Connector Type Multi Tap 3/8 Hex Key Insulation Insulation Type Plastisol Aluminum Material Number Of Ports Physical Attribute - Number of 14 Physical Attribute - Screw Type Allen Plated Plating Type Unplated Temperature Rating UNITAP™ Trade Name UPC 781810233122 UPC 12 Digit 7818102331222

69 mm

Dimensions

Dimension - Height inch

Dimension - Height mm

Dimension - L Length Overall

The state of the s

Electrical Ratings

Dimension - Width mm



Operating Voltage	600 V
Voltage - Maximum	600 V

Conductor Related

Conductor - AL Str Size Range	2 AWG - 750 kcmil
Conductor - Copper Str Size	2 AWG - 750 kcmil
Range	
Conductor Size	2 AWG-750 KCMIL
Conductor Type	 AL C Str-Size
	 CU C Str-Size

Certifications And Compliance

Buy American Compliant	Contact Manufacturer
Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Listed Direct	No
Burial	
Certification - UL Recognized	No
Certification - cULus	No
Certified Listed	BABA Compliant (All status
	valid till December 2024)
Industry Standard(s)	UL 486A-486B
Standards - Industry Standards	UL 486A-486B
Met	
Standards - RoHS Compliance	CM
Status	
UL Listed	No

Minimum Pack Quantity Product Assets

Logistics

Catalogs - UNITAP™ Products
Catalogs - BURNDY Master Catalog - Section A - Mechanical
Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog
Customer Notices - Prop 65 Notice
Interactive Catalog - BURNDY Full-Line Digital Catalog
Product Cross Section Image(s) - BUR_BIBS_Lineart
Sales Drawings - sc210991-15
Specifications - BIBS75014

