

BISR4DB, Direct Burial Insulated Slice Reducer

By Burndy Catalog # BISR4DB

In-Line Splice/Reducer, 2 Port, 6-4 AWG, Al/Cu Rated.



Features

- Type BISR In-Line Splice/Reducers are easily installed on code conductor
- UL486B Listed, Dual rated AL9CU for any stranded copper or stranded aluminum applications

Application

For Outside Direct Burial

General

Connector Type In-Line **EU RoHS Indicator** Yes Hex Key 1/8 in Installation Torque 50 in-lb

Recommended in-lb

Insulation Insulation Type Plastisol Material Aluminum Aluminum Material - Hardware

Number Of Ports Physical Attribute - Number of 2

Screws

Physical Attribute - Screw Allen

Type

Plated

Unplated Plating Type Sub Brand UNITAP, MOLE

Temperature Rating 90 °C Trade Name UNITAP™ **BISR** Type

UPC 781810288054 UPC 12 Digit 7818102880544

4.3 in

Dimensions

Dimension - Height fraction 1.4 in 1.39 in Dimension - Height inch Dimension - L Length Overall 109.22 mm

mm

Dimension - Length Overall

inch

Dimension - Screw Size inch 1/4 Dimension - Strip Length inch 7/8 in Dimension - Width fraction 4/5 in Dimension - Width inch 0.6 in Dimension - Width mm 17.27 mm

Electrical Ratings

Operating Voltage 600 V Voltage - Maximum 600 V

Conductor Related

Conductor - AL Str Size 6 AWG;4 AWG Conductor - AL Str Size 6 AWG - 4 AWG

Range

Conductor - Copper Str Size #6 AWG;5 AWG;#4 AWG

Conductor - Copper Str Size 6 AWG - 4 AWG

Range

Conductor Size 6-4 AWG

Conductor Type · AL C Str-Size

• CU C Str-Size

Certifications And Compliance

Certification - CSA Approved Certification - UL Listed Direct Yes

Burial

Industry Standard(s) UL 486A-486B Standards - Industry UL 486A-486B

Standards Met

Standards - RoHS Compliance

Status

UL Listed Yes

Logistics

Minimum Pack Quantity 1

Product Assets

3D Models - BISR4DB MODEL-STEP 3D Models - BISR4DB_MODEL-PDF 3D Models - BISR4DB_MODEL-IGES

Catalogs - UNITAP™ Products

Catalogs - Full Line BURNDY Catalog

Product Cross Section Image(s) - BUR_BISR_Lineart

Sales Drawings - 10003179

