

BITO350FX, Opposite Side Flex Rated Two Conductor Clear Insulated Multi-Tap Connector

By Burndy Catalog # BITO350FX

Aluminum UNITAP, Tap - Opposite Side Entry, #10-350 Class B & C, #10-250 Class G,H,I,K, DLO, 2 PORT.

Features

- Type BIT-FX and BITO-FX Multi-tap connectors are quickly and easily installed
- UL486B Listed, Dual rated AL9CUFor stranded copper or stranded aluminum applications

General

Catalog Number BITO350FX
Color Code Red
Connector Type Multi Tap
Hex Key 5/16 in
Insulation Y
Material Aluminum

Number Of Ports 2 Plated Y

Plating Type Tin Plated
Temperature Rating 135°C
Trade Name UNITAP™
UPC 621945440661
UPC 12 Digit 6219454406611

Dimensions

Dimension - Height inch

Dimension - Height mm

Dimension - L Length Overall

56.39 mm

mm

Dimension - Length Overall 2.22 in

inch

Dimension - Width inch 2.75 in
Dimension - Width mm 69.85 mm

Electrical Ratings

Operating Voltage 600 V Voltage - Maximum 600 V

Conductor Related



Conductor - AL Str Size Range 10 AWG - 350 kcmil Conductor - Copper DLO Size 10 str.- 250 kcmil

Range

Conductor - Copper Flex G Size 10 str.- 250 kcmil

Range

Conductor - Copper Flex H Size 10 str.- 250 kcmil

Range

Conductor - Copper Flex I Size 10 str.- 250 kcmil

Range

Conductor - Copper Flex K Size 10 str.- 250 kcmil

Range

Conductor - Copper Str Size 10 AWG - 350 kcmil

Range

Conductor Size 10 AWG-350 KCMIL
Conductor Type • AL C Str-Size
• CU C Str-Size

CU C Flex-Size

Certifications And Compliance

Certification - CSA Approved Yes

Industry Standard(s) UL 486A-486B Standards - Industry Standards UL 486A-486B

Met

Standards - RoHS Compliance CM

Status

UL Listed Yes

Logistics

Minimum Pack Quantity 1

Product Assets

Catalogs - UNITAP $^{\text{\tiny{TM}}}$ Products

Catalogs - BURNDY Master Catalog - Section A - Mechanical Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog

Customer Notices - Prop 65 Notice

Interactive Catalog - BURNDY Full-Line Digital Catalog

Sales Drawings - 50046931 Specifications - BITO350FX

