



BYNA451RTACCC, Terminal Pad Assembly, 540mm ACCC, 230kV

By Burndy
Catalog # [BYNA451RTACCC](#)



HYLUG™ Terminal Pad Assembly (ACCC), 540mm² ACCC, 230kV.

General

Catalog Number	BYNA451RTACCC
Connector Type	Terminal
Die Index	725
Feature - Barrel Style	Tapered
Installation Torque	300 in-lb
Recommended in-lb	
Material	Aluminum
Physical Attribute - Number of Holes	4
Trade Name	HYLUG™
UPC	781810514382
UPC 12 Digit	7818105143822

Dimensions

Dimension - Bolt Size fraction	1/2
Dimension - D inch	3.95 in
Dimension - F Width Center to Center inch	1.75 in
Dimension - Hole Size inch	0.56 in
Dimension - Inside Diameter inch	1.18 in
Dimension - Length Overall inch	15.3 in
Dimension - N inch	0.63 in
Dimension - Outside Diameter inch	1.8 in
Dimension - Pad Width inch	3.22 in
Dimension - Thread Size	1/2
Physical Attribute - Tongue Angle	Straight

Conductor Related

Conductor - ACCC Str Size	540mm ² (Dublin)
Conductor - ACCC Str Size Range	540mm ² (Dublin)

Certifications And Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Carton Quantity	4
Minimum Pack Quantity	1
Pallet Quantity	288

Product Assets

- [3D Models - BYNA451RTACCC_MODEL-IGES](#)
- [3D Models - BYNA451RTACCC_MODEL-PDF](#)
- [3D Models - BYNA451RTACCC_MODEL-STEP](#)
- [Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
- [Customer Notices - Prop 65 Notice](#)
- [Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
- [Sales Drawings - 50068520](#)
- [Specifications - BYNA451RTACCC](#)