



CUW556AE, Deadend Clamp, Aluminum Alloy

By Burndy
Catalog # [CUW556AE](#)

High Strength Aluminium Alloy, Deadend Clamp, 3/0 - 556 kcmil ACSR, 10.4" Length.



Features

- High strength aluminum clamp for deadending primary distribution lines
- Straight-line design with hot stick lifting-eye, pulling-eye
- Captured, angled U-bolts
- Snub-pocket V-shaped, range-taking conductor groove and galvanized steel U-bolts provide high holding strength

General

| | |
|---------------------|----------------------|
| Catalog Number | CUW556AE |
| Connector Type | Deadend |
| Material | Aluminum Alloy |
| Material - Hardware | Galvanized Steel |
| Plated | Y |
| Plating Type | Tin - Electro Plated |
| UPC | 781810434550 |

Dimensions

| | |
|---------------------------------|------------|
| Dimension - Height fraction | 4-1/2 in |
| Dimension - Height inch | 4.5 in |
| Dimension - Height mm | 114.3 mm |
| Dimension - L Length Overall mm | 264 mm |
| Dimension - Length Overall inch | 10.4 in |
| Dimension - Width fraction | 3-65/67 in |
| Dimension - Width inch | 3.97 in |

Dimension - Width mm 101 mm

Conductor Related

Conductor - AL Str Size 3/0;4/0;250;266.8;300;336.4;350;397.5;4

Certifications And Compliance

| | |
|------------------------------------|----|
| Certification - CSA Approved | No |
| Certification - ETL | No |
| Certification - UL Recognized | No |
| Certification - cULus | No |
| Standards - RoHS Compliance Status | CM |
| UL Listed | No |

Logistics

Minimum Pack Quantity 22

Product Assets

- [Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
- [Customer Notices - Prop 65 Notice](#)
- [Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
- [Literature - Ropes Course Industry Letter \(April 2021\)](#)
- [Sales Drawings - CSC.029696-01](#)
- [Specifications - CUW556AE](#)