

CY4/0L17G5TN Rope Lay Braid

By Burndy Catalog # CY4/0L17G5TN

Tin Plated Ferrules.



- Most Burndy braid are UL Listed and CSA Certified
- Pressed seamless copper ferrules provide added durability and prevent fraying, providing extra strength for a robust bonding connection
- Braid is especially suited for applications that require flexibility or resistance to vibration
- Extra fine stranding gives enhanced flexibility
- Ferrules clearly marked with Burndy braid type and UL markings (where appropriate)
- Available in custom lengths and hole sizes to suit your needs (contact your local sales representative for non-standard configurations)
- For assistance in finding the perfect braid for your needs click here for our Braid Configurator Tool: www.hubbell.com/config/BRAID

General

CY4/0L17G5TN
Braid
Copper
781810665336
7818106653366

Dimensions

Dimension - L Length Overall	432 mm
mm	
Dimension - Length Overall	17 in
inch	



Length	
Weight	

17 in 0.235 lb

Electrical Ratings

Amperage Rating 335 A

Certifications And Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance	UI
Status	
UL Listed	No

Logistics

Carton Quantity	20
Minimum Pack Quantity	40
Pallet Quantity	1920

Product Assets

Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog Customer Notices - Prop 65 Notice Interactive Catalog - BURNDY Full-Line Digital Catalog Sales Drawings - 50038434 Specifications - BURNDY_CY40L17G5TN_Specsheet Specifications - CY4/0L17G5TN

