

FD675D12BRTN, Substation -Copper Stud Connector

By Burndy Catalog # FD675D12BRTN

Copper Stud Connectors.

Application


Substation

General

| Catalog Number | FD675D12BRTN |
|--------------------------------|-----------------------------|
| Connector Type | Stud Connector |
| Material | Copper Alloy |
| Material - Hardware | DURIUM [™] Silicon |
| Physical Attribute - Number of | 4 |
| Holes | |
| Physical Attribute - Pad | 4x4 - 4 holes |
| Configuration | |
| Physical Attribute - Pad | In-line |
| Orientation | |
| Plated | Y |
| Plating Type | Tin - Bright |
| Туре | Studs |
| UPC | 781810338247 |
| UPC 12 Digit | 7818103382477 |

Dimensions

| Dimension - B Length inch | 2.18 in |
|---|----------------|
| Dimension - Bolt Size fraction | 1/2 |
| Dimension - D inch | 4.00 in |
| Dimension - F Width Center to | 1.75 in |
| Center inch | |
| | |
| Dimension - Height mm | 0 mm |
| Dimension - Height mm Dimension - L Length Overall | 0 mm 188 mm |
| 0 | 0 |
| Dimension - L Length Overall | 0 |



| Dimension - N inch | 1.13 in |
|-------------------------------|----------|
| Dimension - Pad Width inch | 4.00 in |
| Dimension - Pin Diameter | 1-3/4 in |
| fraction | |
| Dimension - Pin Diameter inch | 1.750 in |
| Dimension - Thread Size | 1/2-12 |
| Dimension - Threads per inch | 12 |

Conductor Related

Bronze

Conductor - Connection Stud to Pad Combination

Certifications And Compliance

| Certification - CSA Approved | No |
|-------------------------------|----|
| Certification - ETL | No |
| Certification - UL Recognized | No |
| Certification - cULus | No |
| Standards - RoHS Compliance | ΕX |
| Status | |
| UL Listed | No |
| | |

Logistics

Minimum Pack Quantity 2

Product Assets

Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog Customer Notices - Prop 65 Notice Interactive Catalog - BURNDY Full-Line Digital Catalog Sales Drawings - SD079583 Specifications - FD675D12BRTN

