

GAR3903BU, Mechanical Grounding Connector, Conductor to Water Pipe

By Burndy Catalog # GAR3903BU

Mechanical Grounding Connector, Conductor to Water Pipe, 4-4/0 AWG, 1-1/4"-2" Pipe, 3/8" Stud.



Application

For Connecting A Small To Medium Range Copper Ground Conductor To Water Pipe As Well As Structural And Reinforcing Rod Shapes

General

EU RoHS Indicator Yes

Installation Torque 200 LBS/in

Recommended in-lb

Material Copper Alloy

Material - Hardware DURIUM™ Silicon Bronze

Plated

Plating Type Unplated

Sub Brand MECHANICAL CONNECTOR

Type GAR-BU U Bolt Type 1032

UPC 781810001509 UPC 12 Digit 7818100015099

Dimensions

Dimension - B Length inch

Dimension - Height inch

4.00 in

Dimension - Length Overall

1.75 in

inch

Dimension - Outside Diameter 2.38 in

inch

Dimension - Width inch 4.25 in
Dimension - Width mm 108 mm

Conductor Related

Conductor - Copper Solid Size 4 AWG - 4/0 AWG

Range

Conductor - Copper Str Size 4;3;2;1;1/0;2/0;3/0;4/0

Conductor - Copper Str Size 4-4/0

Range

Conductor - Copper Tube Std 11/4;2

Size

Conductor - Copper Tube Std 11/4-2

Size Range

Conductor - Pipe or Round 1.25 - 2 in

Tube Size

Certifications and Compliance

Certification - CSA Approved No
Certification - ETL No
Certification - UL Listed Direct Yes

Burial

Certification - UL Recognized No
Certification - cULus No
Industry Standard(s) UL467
Standards - Industry UL467

Standards Met

Standards - RoHS Compliance CM

Status

Logistics

Minimum Pack Quantity 1

Product Assets

3D Models - GAR3903BU_MODEL-PDF 3D Models - GAR3903BU_MODEL-IGES 3D Models - GAR3903BU_MODEL-STEP

Customer Notices - Prop 65 Notice

Sales Drawings - sd206396

