

GD2129, Mechanical Grounding Connector, 2 Cables to Rod or Pipe

By Burndy Catalog # GD2129



Mechanical Grounding Connector, 2 Parallel Cables to Rod or Pipe, 2/0 AWG (Sol.) - 250 kcmil, 3-1/2" to 4" Rod, 3-1/2" Pipe.

Features

- Rated for Direct Burial in earth or concrete
- UL467 Listed for the US and Canadian Markets
- One-wrench installation

Application

For Joining A Range Of Two Parallel Copper Cables To Rod Or Pipe And Burial In Ground Or Concrete

General

Catalog Number
EU RoHS Indicator
Installation Torque
Recommended in-lb
Material
Material Type - Screw
Plated
Plating Type
Sub Brand
Туре
U Bolt Type
UPC
UPC 12 Digit

GD2129 Yes 240 LBS/in

Copper Alloy, Cast DURIUM[™] Silicon Bronze N Unplated MECHANICAL CONNECTOR GD 264 781810260432 7818102604322

Dimensions

Dimension - B Length inch
Dimension - Height fraction
Dimension - Height inch
Dimension - Width fraction
Dimension - Width inch
Dimension - Width mm

1.50 in 6-1/4 in 6.25 in 5-3/8 in 5.31 in 135 mm

Conductor Related

2/0;3/0;4/0
2/0-4/0
2/0;3/0;4/0;250
3.5
2/0 AWG - 250 kcmil
3-1/2
3-1/2
2/0 AWG Sol - 250 kcmil

Certifications And Compliance

Buy American Compliant	Yes
Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Listed Direct	Yes
Burial	
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL467
Standards - Industry Standards	UL467
Met	
Standards - RoHS Compliance	EX
Status	
UL Listed	Yes

Logistics

Minimum Pack Quantity 1

Product Assets

3D Models - GD2129_MODEL-STEP 3D Models - GD2129_MODEL-PDF 3D Models - GD2129_MODEL-IGES Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog Catalogs - BURNDY Master Catalog - Section E2 - Mechanical Grounding Customer Notices - Prop 65 Notice Interactive Catalog - BURNDY Full-Line Digital Catalog Product Cross Section Image(s) - BUR_gdla Sales Drawings - SD..013775-01 Specifications - GD2129



(HUBBELL) A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved BRDY-GD2129-SPEC-EN | REV 8/2024