

GG202, Mechanical Grounding Connector, Copper Bar, Strap, Braid, or Cable to Rod or Tube

By Burndy Catalog # GG202

Mechanical Grounding Connector, Copper Bar, Strap, Braid or Cable to Rod or Tube, 3" Pipe, 3"-3-1/2" Rod.

Features

- High copper alloy ground connector for joining bar, strap, braid or cable to rod or tube
- Rated for Direct Burial in earth or concrete
- UL467 Listed
- One wrench installation
- Type GG connector is particularly effective for use with braid for ground rods, switch handles, fence posts and gates

Application

For Joining Copper Bar, Strap, Braid Or Cable To Rod Or Tube, Direct Burial Cables

General

Catalog Number GG202 EU RoHS Indicator Yes

Installation Torque 480 LBS/in

Recommended in-lb

MaterialCopper Alloy, CastMaterial Type - ScrewDURIUM™ Silicon Bronze

Plated

Plating Type Unplated

Sub Brand MECHANICAL CONNECTOR

Type GG U Bolt Type 282

UPC 781810238998 UPC 14 Digit GTIN 00781810238998

Dimensions

Dimension - B Length inch

Dimension - Height mm

Dimension - Width fraction

1.88 in

162.1 mm

5-1/5 in



Dimension - Width inch 5.19 in
Dimension - Width mm 132 mm

Certifications And Compliance

Buy America(n) Qualified Contact Manufacturer

Certification - CSA Approved No Certification - ETL No Certification - UL Listed Direct Yes

Burial

Certification - UL Recognized No
Certification - cULus No
Industry Standard(s) UL467
Standards - Industry Standards UL467

Met

Standards - RoHS Compliance EX

Status

UL Listed No

Logistics

Minimum Pack Quantity 1

Product Assets

3D Models - GG202_MODEL-IGES
3D Models - GG202_MODEL-PDF
3D Models - GG202_MODEL-STEP
Catalogs - Burndy Grounding Catalog

Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog

Customer Notices - Prop 65 Notice

Interactive Catalog - BURNDY Full-Line Digital Catalog Product Cross Section Image(s) - BUR GG LineArt

Sales Drawings - sd013776-01

Specifications - GG202

