



# GP2226, Mechanical Grounding Connector, 2 Cables to Rod or Pipe

By Burndy  
Catalog # [GP2226](#)



Mechanical grounding connector, 4 AWG Solid - 2/0 AWG Stranded, 4" Pipe, 4" Rod, 240 LBS/in Installation Torque.

### Features

- Rated for Direct Burial in earth or concrete
- UL467 Listed for the US and Canadian Markets
- One-wrench installation

### General

Catalog Number	GP2226
Installation Torque	240 LBS/in
Recommended in-lb	
Material	Copper Alloy
Material Type - Screw Plated	DURIUM™ Silicon Bronze
Plating Type	N
U Bolt Type	Unplated
U Bolt Type	261
UPC	781810001653
UPC 14 Digit GTIN	00781810001653

### Dimensions

Bolt Size	3/8 in
Dimension - B Length inch	4.50 in
Dimension - Height mm	162.1 mm
Dimension - L Length Overall mm	43 mm
Dimension - Length Overall inch	1.69 in
Dimension - Width fraction	5-13/16 in
Dimension - Width inch	5.81 in
Dimension - Width mm	148 mm

### Conductor Related

Conductor - Copper Solid Size Range	4-3/0
Conductor - Copper Str Size Range	5 AWG - 2/0 AWG

Conductor - Rod Size	4 in
Conductor Size	#4 Sol AWG - 2/0 Str AWG

### Certifications And Compliance

Buy America(n) Qualified	Contact Manufacturer
Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Listed Direct Burial	Yes
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL467
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance	CM
Status	
UL Listed	Yes

### Logistics

Minimum Pack Quantity	4
-----------------------	---

### Product Assets

- [3D Models - GP2226\\_MODEL-STEP](#)
- [3D Models - GP2226\\_MODEL-IGES](#)
- [3D Models - GP2226\\_MODEL-PDF](#)
- [Catalogs - Burndy Grounding Catalog](#)
- [Catalogs - BURNDY Master Catalog - Section E2 - Mechanical Grounding](#)
- [Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
- [Customer Notices - Prop 65 Notice](#)
- [Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
- [Product Cross Section Image\(s\) - BUR\\_gpla](#)
- [Sales Drawings - SD..013778-02](#)
- [Specifications - GP2226](#)