

GRC34, Mechanical Ground Rod Clamp, Cable to Rod

By Burndy Catalog # GRC34

Mechanical Ground Rod Clamp, For Cable to Rod, High Strength, 8 AWG (Sol.) - 1/0 AWG (Str.), 3/4" Ground Rod, 3/8" Stud.

Features

- Rated for Direct Burial in earth or concrete
- UL 467 Listed for the US and Canadian Markets

Application

For Joining A Range Of Cable To Copper Clad, Galvanized Steel, And Stainless Steel Ground Rods, Direct Burial Applications In Earth And Concrete

General

Catalog Number	GRC34
EU RoHS Indicator	Yes
Hardware Type	Silicon Bronze
Material	Copper Alloy
Material - Hardware	Silicon Bronze
Plated	N
Plating Type	Unplated
Sub Brand	MECHANICAL CONNECTOR
Туре	GRC, High Strength
UPC	781810230985
UPC 12 Digit	7818102309855

Dimensions

Dimension - B Length inch0.65 inDimension - Height inch2.40 inDimension - Length Side B inch0.65 inDimension - Width inch1.09 inDimension - Width mm28 mm

Conductor Related

Conductor - Copper Solid Size	8 AWG
Range	
Conductor - Copper Str Size	8 AWG - 1/0 AWG
Range	
Conductor - Rod Size	3/4 in
Conductor Size	#8 AWG Sol - 1/0 AWG Str
Conductor Type	 Rod-Size
	CU C Solid-Size



Certifications And Compliance

Buy American Compliant	No
Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Listed Direct	Yes
Burial	
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL467
Standards - Industry Standards	UL467
Met	
Standards - RoHS Compliance	СМ
Status	
UL Listed	Yes

Logistics

Carton Quantity	100
Minimum Pack Quantity	1
Pallet Quantity	27500

Product Assets

3D Models - GRC34_MODEL-IGES 3D Models - GRC34_MODEL-PDF 3D Models - GRC34_MODEL-STEP Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog Catalogs - BURNDY Master Catalog - Section E2 - Mechanical Grounding Customer Notices - Prop 65 Notice Interactive Catalog - BURNDY Full-Line Digital Catalog Product Cross Section Image(s) - BUR_GRC_Lineart Sales Drawings - SA..076868-01



HUBBELL A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved BRDY-GRC34-SPEC-EN | REV 8/2024