

HSC18FR250, PVC Clear Heat Shrink Tubing, #14-#16 Code & Flex, 600 V, Fire Retardant.

By Burndy Catalog # HSC18FR250

PVC Clear Heat Shrink Tubing, #14-#16 Code & Flex, 600 V, Fire Retardant.



For Terminations And Splices

General

Catalog Number HSC18FR250

Clear

CLEAR TUBES Connector Type

EU RoHS Indicator

Material Polyvinyl chloride Sub Brand VISISHRINK VISI-SHRINK™ Trade Name

HSC-FR, Thin Wall, Flexible, Туре

Fire Retardant

UPC 781810266229

Conductor Related

Conductor Range #16 AWG to #14 AWG

Conductor Size 16AWG - 14AWG

Certifications And Compliance



Buy American Compliant Yes Certification - CSA Approved Certification - ETL No Standards - RoHS Compliance СМ

Status

UL Listed No

Logistics

Minimum Pack Quantity

Product Assets

Catalogs - BURNDY Master Catalog - Section D - Shrink Tubing Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog

Interactive Catalog - BURNDY Full-Line Digital Catalog

Literature - Polyolefin Thin Wall Heat Shrink Cross Reference

Guide

Product Cross Section Image(s) - BUR_HSC100FR_LineArt

Sales Drawings - 50015598 Specifications - HSC18FR250

Video - Heat Shrink Product Overview & Installation

