

# HSTPBK00471000FRL, Thin Wall Polyolefin Heat Shrink Tubing, Black, 1000' Reel, 3/64" ID

By Burndy Catalog # HSTPBK00471000FRL

3/64 I.D., 1 Unit = 1000 Ft., Color = Black, 2:1 Ratio, Thin Wall Polyolefin Heat Shrink, 600V Max, Shrink Temp 90°C Min, -55°C To 135°C Continuous Operating Temp, Store At 21°C.

#### **Features**

- Ideal for industrial and automotive applications as well as covering copper and aluminum tubular connectors
- Provides mechanical protection for terminal strain relief and wire bonding
- 2:1 shrink ratio for faster shrink recovery
- Continuous Operating Temperature: -55°C to 135°C (-67°F to 275°F)
- Shrink temperature of 90°C
- Resistant to common fluids and solvents

#### General

Catalog Number HSTPBK00471000FRL

Color Black



UPC 621945689824

## Logistics

Carton Quantity

### **Product Assets**

Brochures - Polyolefin Thin Wall Heat Shrink Brochure
Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog
Interactive Catalog - BURNDY Full-Line Digital Catalog
Literature - Distributor Promotion: HS-TP Thin Wall Polyolefin
Heat Shrink Expires 12-31-2024
Literature - Polyolefin Thin Wall Heat Shrink Cross Reference

Literature - Polyolefin Thin Wall Heat Shrink Cross Referen-Guide

Sales Drawings - 50139507

Specifications - HSTPBK00471000FRL

