HSTPBK0125250FRL, Thin Wall Polyolefin Heat Shrink Tubing, Black, 250′ Reel, 1/8″ ID

By Burndy
Catalog # HSTPBK0125250FRL

1/8 I.D., 1 Unit = 250 Ft., Color = Black, 2:1 Ratio, Thin Wall Polyolefin Heat Shrink, 600V Max, Shrink Temp 90°C Min, -55°C To 135°C Continuous Operating Temp, Store At 21°C.

Features

- Ideal for industrial and automotive applications as well as covering copper and aluminum tubular connectors
- Provides mechanical protection for terminal strain relief and wire bonding
- 2:1 shrink ratio for faster shrink recovery
- Continuous Operating Temperature: -55°C to 135°C (-67°F to 275°F)
- Shrink temperature of 90°C
- Resistant to common fluids and solvents

General

Catalog Number	HSTPBK0125250FRL
Color	Black
UPC	621945691919

Logistics

Carton Quantity	4

Product Assets

Brochures - Polyolefin Thin Wall Heat Shrink Brochure
Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog
Interactive Catalog - BURNDY Full-Line Digital Catalog
Literature - Distributor Promotion: HS-TP Thin Wall Polyolefin Heat Shrink Expires 12-31-2024
Literature - Polyolefin Thin Wall Heat Shrink Cross Reference Guide
Sales Drawings - 50139507
Specifications - HSTPBK0125250FRL

©2024 Hubbell Incorporated. All rights reserved