

# HSTPBL400025FRL, Thin Wall Polyolefin Heat Shrink Tubing, Blue, 25' Reel, 4" ID

By Burndy Catalog # HSTPBL400025FRL

4 I.D., 1 Unit = 25 Ft., Color = Blue, 2:1 Ratio, Thin Wall Polyolefin Heat Shrink, 600V Max, Shrink Temp 90°C Min, -55°C To 135°C Continuous Operating Temp, Store At 21°C.

## Features

- Ideal for industrial and automotive applications as well as covering copper and aluminum tubular connectors
- Provides mechanical protection for terminal strain relief and wire bonding
- 2:1 shrink ratio for faster shrink recovery
- Continuous Operating Temperature: -55°C to 135°C (-67°F to 275°F)
- Shrink temperature of 90°C
- Resistant to common fluids and solvents

## General

Catalog Number Color HSTPBL400025FRL Blue



UPC

621945697812

## Logistics

Carton Quantity

## **Product Assets**

Brochures - Polyolefin Thin Wall Heat Shrink Brochure Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog Interactive Catalog - BURNDY Full-Line Digital Catalog Literature - Distributor Promotion: HS-TP Thin Wall Polyolefin Heat Shrink Expires 12-31-2024 Literature - Polyolefin Thin Wall Heat Shrink Cross Reference Guide Specifications - HSTPBL400025FRL

2



©2024 Hubbell Incorporated. All rights reserved BRDY-HSTPBL400025FRL-SPEC-EN | REV 10/2024