

HSTPGR037550FRL, Thin Wall Polyolefin Heat Shrink Tubing, Green, 50' Reel, 3/8" ID

By Burndy Catalog # HSTPGR037550FRL

3/8 I.D., 1 Unit = 50 Ft., Color = Green, 2:1 Ratio, Thin Wall Polyolefin Heat Shrink, 600V Max, Shrink Temp 90°C Min, -55°C To 135°C Continuous Operating Temp, Store At 21°C.



- Ideal for industrial and automotive applications as well as covering copper and aluminum tubular connectors
- Provides mechanical protection for terminal strain relief and wire bonding
- 2:1 shrink ratio for faster shrink recovery
- Continuous Operating Temperature: -55°C to 135°C (-67°F to 275°F)
- Shrink temperature of 90°C
- Resistant to common fluids and solvents

General

Catalog Number HSTPGR037550FRL

Color Green



UPC 621945694200

Logistics

Carton Quantity 10

Product Assets

Brochures - Polyolefin Thin Wall Heat Shrink Brochure
Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog
Interactive Catalog - BURNDY Full-Line Digital Catalog
Literature - Distributor Promotion: HS-TP Thin Wall Polyolefin
Heat Shrink Expires 12-31-2024

Literature - Polyolefin Thin Wall Heat Shrink Cross Reference Guide

Sales Drawings - 50139507

Specifications - HSTPGR037550FRL

