

HSTPMX10006IPK25, Thin Wall Polyolefin Heat Shrink Tubing, Mixed, 25-Pack, 6" Lengths, 1" ID

By Burndy Catalog # HSTPMX10006IPK25

1 I.D., 1 Unit = 1 Pk Of 25, Color = Mixed, 2:1 Ratio, Thin Wall Polyolefin Heat Shrink, 600V Max, Shrink Temp 90°C Min, -55°C To 135°C Continuous Operating Temp, Store At 21°C.

Features

- Ideal for industrial and automotive applications as well as covering copper and aluminum tubular connectors
- Provides mechanical protection for terminal strain relief and wire bonding
- 2:1 shrink ratio for faster shrink recovery
- Continuous Operating Temperature: -55°C to 135°C (-67°F to 275°F)
- Shrink temperature of 90°C
- Resistant to common fluids and solvents

General

Catalog Number Color HSTPMX10006IPK25 Multiple Colors



UPC

621945696068

Logistics

Carton Quantity

Product Assets

Brochures - Polyolefin Thin Wall Heat Shrink Brochure Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog Catalogs - BURNDY Master Catalog - Section D - Shrink Tubing Interactive Catalog - BURNDY Full-Line Digital Catalog Literature - Distributor Promotion: HS-TP Thin Wall Polyolefin Heat Shrink Expires 12-31-2024 Sales Drawings - 50139507 Specifications - HSTPMX10006IPK25

8

