

HSTPYG037550FRL, Thin Wall Polyolefin Heat Shrink Tubing, Yellow/Green, 50' Reel, 3/8" ID

By Burndy Catalog # HSTPYG037550FRL

3/8 I.D., 1 Unit = 50 Ft., Color = Yellow/Green, 3:1 Shrink Ratio, Thin Wall Polyolefin Heat Shrink, 600V Max, Shrink Temp 90°C Min, -55°C To 135°C Continuous Operating Temp, Store At 21°C.

Features

- Ideal for industrial and automotive applications as well as covering copper and aluminum tubular connectors
- Provides mechanical protection for terminal strain relief and wire bonding
- 3:1 shrink ratio for faster shrink recovery
- Continuous Operating Temperature: -55°C to 135°C (-67°F to 275°F)
- Shrink temperature of 90°C
- Resistant to common fluids and solvents

General

Catalog Number Color HSTPYG037550FRL Yellow/Green



UPC

621945694545

Logistics

Carton Quantity

Product Assets

Brochures - Polyolefin Thin Wall Heat Shrink Brochure Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog Interactive Catalog - BURNDY Full-Line Digital Catalog Literature - Distributor Promotion: HS-TP Thin Wall Polyolefin Heat Shrink Expires 12-31-2024 Literature - Polyolefin Thin Wall Heat Shrink Cross Reference Guide Specifications - HSTPYG037550FRL

10



©2024 Hubbell Incorporated. All rights reserved BRDY-HSTPYG037550FRL-SPEC-EN | REV 10/2024