

K2C17, SERVIT POST Mechanical Connector, 2 Cables to Flat

By Burndy Catalog # K2C17





Application

For Used To Ground One Or Two Copper Cables To Steel Structures, Fence Posts, Transformers, Tap One Or Two Cables From Bus Bar And Direct Burial

General

Catalog Number K2C17 EU RoHS Indicator Yes

Material Bronze Alloy, Leaded

Plated N

Plating Type Unplated Stud Installation Torque inch 80 LBS/in

pounds

Sub BrandSERVIT POSTTrade NameSERVIT POST™TypeKC and K2C SeriesUPC781810256909UPC 12 Digit7818102569099

Dimensions

Dimension - B Length fraction 3/8 in Dimension - B Length inch 0.37 in Dimension - Body Width inch 0.44 in Dimension - Bolt Size fraction 1/4 Dimension - D inch 0.50 in Dimension - Height fraction 7/8 Dimension - Height inch 1.00 in Dimension - L Length Overall 34.0 mm

mm

Dimension - Length Overall 1.34 in

inch

Dimension - Nut Width inch

Dimension - P inch

Dimension - Threads per inch

Dimension - Width inch

25 mm

Conductor Related

Conductor - Copper Solid Size 10 AWG;9 AWG;8 AWG;7

AWG;6 AWG

Conductor - Copper Solid Size 6 AWG - 10 AWG

Range

Conductor - Copper Str Size 10 AWG;9 AWG;8 AWG;7 AWG

Conductor - Copper Str Size 7 AWG - 10 AWG

Range

Physical Attribute - Number of 2 Conductors Accommodated

Total

Certifications And Compliance

Buy American Compliant Yes
Certification - CSA Approved No
Certification - ETL No
Certification - UL Listed Direct Yes

Burial

Certification - UL Recognized No
Certification - cULus No
Industry Standard(s) UL467
Standards - Industry Standards UL467

Met

Standards - RoHS Compliance EX

Status

UL Listed Yes

Logistics

Carton Quantity 50
Minimum Pack Quantity 1
Pallet Quantity 44550

Product Assets

Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog Catalogs - BURNDY Master Catalog - Section E2 - Mechanical Grounding

Customer Notices - Prop 65 Notice Interactive Catalog - BURNDY Full-Line Digital Catalog Product Cross Section Image(s) - BUR_K2C_Lineart

Sales Drawings - SD..055917 Specifications - K2C17

