



# KAPO1/0, Wire range: #6 - 1/0 AWG, Torque: 100 N lb, Voltage: 600 V.

By Burndy  
Catalog # KAPO1/0

Wire range: #6 - 1/0 AWG, Torque: 100 N lb, Voltage: 600 V.



### Features

- 
- 
- 
- 
- 
- 

### Application

Terminate "upsized" conductor and/or fine strand conductor into mechanical connectors found in molded case circuit breakers, panel board equipment, and other switchgear.

### General

Connector Type	Offset
EU RoHS Indicator	Contact Manufacturer
Hex Key	1/4 in
Installation Torque Recommended in-lb	100
Material	Aluminum
Sub Brand	Pin Adaptor
Type	#6 - 1/0 Mechanical Pin Adaptor; Off-Centered Pin
UPC	621945493353

### Dimensions

Dimension - Strip Length inch	.97 in
Dimensions	2.01 in x 1.12 in x 1.43 in
Height	1.43 in
Length	2.01 in
Outside Diameter	1 in
Width	1.12 in

### Electrical Ratings

Amperage Rating	170 A
-----------------	-------

### Conductor Related

Conductor - AL Str Size Range	6 AWG - 1/0 AWG
Conductor - Copper DLO Size Range	6 AWG - 1/0 AWG
Conductor - Copper Flex H Size Range	6 AWG - 1/0 AWG
Conductor - Copper Flex I Size Range	6 AWG - 1/0 AWG
Conductor - Copper Flex K Size Range	6 AWG - 1/0 AWG
Conductor - Copper Str Size Range	6 AWG - 1/0 AWG
Conductor Size	6-1/0 AWG

### Logistics

Carton Quantity	30
Minimum Pack Quantity	1
Pallet Quantity	2700

### Product Assets

[Catalogs - Full Line BURNDY Catalog](#)  
[Customer Notices - Prop 65 Notice](#)  
[Sales Drawings - 50076514](#)



A proud member of the Hubbell Family.