



# KAPO350, 350 Kcmil pin adaptor, Torque: 500 N lb, Voltage: 600 V.

By Burndy  
Catalog # [KAPO350](#)

350 Kcmil pin adaptor, Torque: 500 N lb, Voltage: 600 V.



**Features**

- 
- 
- 
- 
- 
- 

**Application**

Terminate "upsized" conductor and/or fine strand conductor into mechanical connectors found in molded case circuit breakers, panel board equipment, and other switchgear.

**General**

|                     |  |
|---------------------|--|
| Connector Type      | Offset   |
| EU RoHS Indicator   | Contact Manufacturer                               |
| Hex Key             | 3/8 in   |
| Installation Torque | 450  |
| Recommended in-lb   |  |
| Material            | Aluminum   |
| Sub Brand           | Pin Adaptor  |
| Type                | 1/0 - 350 Mechanical Pin Adaptor; Off-Centered Pin |
| UPC                 | 621945493360                                       |

**Dimensions**

|                               |                             |
|-------------------------------|-----------------------------|
| Dimension - Strip Length inch | 1.11 in                     |
| Dimensions                    | 2.75 in x 1.50 in x 2.00 in |
| Height                        | 2 in                        |
| Length                        | 2.75 in                     |
| Outside Diameter              | 1.38 in                     |
| Width                         | 1.5 in                      |

**Electrical Ratings**

|                 |       |
|-----------------|-------|
| Amperage Rating | 350 A |
|-----------------|-------|

**Conductor Related**

|                                      |                     |
|--------------------------------------|---------------------|
| Conductor - AL Str Size Range        | 1/0 AWG - 350 kcmil |
| Conductor - Copper DLO Size Range    | 1/0 AWG - 350 kcmil |
| Conductor - Copper Flex H Size Range | 1/0 AWG - 350 kcmil |
| Conductor - Copper Flex I Size Range | 1/0 AWG - 350 kcmil |
| Conductor - Copper Flex K Size Range | 1/0 AWG - 350 kcmil |
| Conductor - Copper Str Size Range    | 1/0 AWG - 350 kcmil |
| Conductor Size                       | 1/0 AWG- 350 KCMIL  |

**Logistics**

|                       |      |
|-----------------------|------|
| Carton Quantity       | 25   |
| Minimum Pack Quantity | 1    |
| Pallet Quantity       | 2250 |

**Product Assets**

[Catalogs - Full Line BURNDY Catalog](#)  
[Customer Notices - Prop 65 Notice](#)  
[Sales Drawings - 50076514](#)



A proud member of the Hubbell Family.