

KC31, SERVIT POST Mechanical Connector, Cable to Flat

By Burndy Catalog # KC31

Mechanical Grounding Connector, Cable to Flat, 1 AWG - 350 AWG (Str), 5/8" Stud.

Application

For Used To Ground One Or Two Copper Cables To Steel Structures, Fence Posts, Transformers, Tap One Or Two Cables From Bus Bar And Direct Burial

General

Catalog Number	KC31
EU RoHS Indicator	Yes
Material	Copper Alloy, Cast
Plated	Ν
Plating Type	Unplated
Stud Installation Torque inch	660 LBS/in
pounds	
Sub Brand	SERVIT POST
Trade Name	SERVIT POST™
Туре	KC and K2C Series
UPC	781810256503
UPC 12 Digit	7818102565033

Dimensions

Dimension - B Length fraction	3/4 in
Dimension - Body Width inch	1.43 in
Dimension - Bolt Size fraction	5/8
Dimension - D inch	1.00 in
Dimension - Height fraction	2-1/4
Dimension - Length Overall	3.19 in
inch	
Dimension - Nut Width inch	1.69 in
Dimension - P inch	0.70 in
Dimension - Threads per inch	11

Conductor Related

Conductor - Copper Str Size	1 AWG;1/0 ;2/0 AWG;3/0
	AWG;4/0 AWG;250 kcmil;300
	kcmil;350 kcmil
Conductor - Copper Str Size	1 AWG-350 kcmil
Range	
Physical Attribute - Number of	1
Conductors Accommodated	
Total	



Certifications And Compliance

Buy American Compliant	Yes
Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Listed Direct	Yes
Burial	
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL467
Standards - Industry Standards	UL467
Met	
Standards - RoHS Compliance	EX
Status	
UL Listed	Yes

Logistics

Minimum Pack Quantity 1

Product Assets

3D Models - KC31_MODEL-STEP 3D Models - KC31_MODEL-IGES 3D Models - KC31_MODEL-PDF Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog Catalogs - BURNDY Master Catalog - Section E2 - Mechanical Grounding Customer Notices - Prop 65 Notice Interactive Catalog - BURNDY Full-Line Digital Catalog Product Cross Section Image(s) - BUR_KC_Lineart Sales Drawings - SD..055917 Specifications - BURNDY_KC31_Specsheet Specifications - KC31



HUBBELL A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved BRDY-KC31-SPEC-EN | REV 8/2024