



KVS26, 2-piece OKLIP Service Connector for heavy duty applications

By Burndy
Catalog # [KVS26](#)



Compact, two-piece, high strength, high copper alloy BURNDY OKLIP recommended for heavy duty connections. Neoprene rings hold DURIUM bolts in place during installation.Installed with ordinary wrench.Recommended tightening torque:180 in-lb.

Application

For Copper, Copperweld

General

EU RoHS Indicator	Yes
Installation Torque Recommended in-lb	180 LBS/in
Material	Copper
Plated	N
Plating Type	Unplated
Sub Brand	OKLIP
Trade Name	OKLIP™
Type	KVS, Compact
UPC	781810061206
UPC 12 Digit	7818100612066

Dimensions

Dimension - Height inch	1.74 in
Dimension - Pad Width inch	1.06 in
Dimension - Stud Size inch	5/16 in
Dimension - Width inch	1.56 in
Dimension - Width mm	40 mm

Conductor Related

Conductor - Copper Solid Tap	6 AWG;5 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 AWG;2/0 AWG
Conductor - Copper Solid Tap Range	6 AWG-2/0 AWG
Conductor - Copper Str Run Range	1 str. 2/0 str.
Conductor - Copper Str Tap Range	6 str. - 2/0 str.
Conductor - CopperWeld Solid Run	3/0
Conductor - CopperWeld Solid Tap	3/0
Conductor Type	<ul style="list-style-type: none">• CU C Str-Run• CU C Str-Tap• CU Weld C Solid-Run• CU Weld C Solid-Tap

Certifications And Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	RUS
Standards - Industry Standards Met	RUS
Standards - RoHS Compliance Status	EX
UL Listed	Yes

Logistics

Minimum Pack Quantity	1
-----------------------	---

Product Assets

[Catalogs - Full Line BURNDY Catalog](#)
[Customer Notices - Prop 65 Notice](#)
[Product Cross Section Image\(s\) - BUR_KVS_Lineart](#)
[Sales Drawings - SC..052062-01](#)



A proud member of the Hubbell Family.

