



# KVS40, 2-piece OKLIP Service Connector for heavy duty applications

By Burndy  
Catalog # [KVS40](#)



Compact, two-piece, high strength, high copper alloy BURNDY OKLIP recommended for heavy duty connections. Neoprene rings hold DURUM bolts in place during installation. Installed with ordinary wrench. Recommended tightening torque: 500 in-lb.

## Application

For Copper And Copperweld, Heavy Duty Connections

## General

EU RoHS Indicator	Yes
Installation Torque Recommended in-lb	500 LBS/in
Material	Copper
Plated	N
Plating Type	Unplated
Sub Brand	OKLIP
Trade Name	OKLIP™
Type	KVS
UPC	781810063903
UPC 12 Digit	7818100639033

## Dimensions

Dimension - Height inch	3.19 in
Dimension - Stud Size inch	1/2 in
Dimension - Width inch	2.50 in

## Conductor Related

Conductor - Copper Str Run Range	400 - 800 kcmil
Conductor - Copper Str Tap Range	3/0 str. - 800 kcmil
Conductor Type	<ul style="list-style-type: none"> <li>• CU C Str-Run</li> <li>• CU C Str-Tap</li> <li>• CU Weld C Solid-Run</li> <li>• CU Weld C Solid-Tap</li> </ul>

## Certifications And Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL486C
Standards - Industry Standards Met	UL486C
Standards - RoHS Compliance Status	CM
UL Listed	Yes

## Logistics

Minimum Pack Quantity	1
-----------------------	---

## Product Assets

- [Catalogs - Full Line BURNDY Catalog](#)
- [Customer Notices - Prop 65 Notice](#)
- [Product Cross Section Image\(s\) - BUR\\_KVS\\_Lineart](#)
- [Sales Drawings - SC..052062-01](#)



A proud member of the Hubbell Family.