

Substation - Copper Terminal

By Burndy Catalog # N2AH2934N

Substation Connectors.



Conductor Related

Conductor - Connection Combination	Cable to Flat	
Conductor - Copper Solid Size	6 AWG;5 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 AWG;2/0 AWG;3/0 AWG;4/0 AWG	
Conductor - Copper Solid Size Range	6 AWG-4/0 AWG	
Conductor - Copper Str Size	6 AWG;5 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 ;2/0 AWG;3/0 AWG;4/0 AWG;250 kcmil	
Conductor - Copper Str Size Range	6 AWG-250 kcmil	
Number of Conductors	2	
Certifications And Compliance		
Certification - CSA Approved	No	

1

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance	ΕX
Status	
UL Listed	No

Logistics

Minimum Pack Quantity

Product Assets

Catalogs - Full Line BURNDY Catalog Customer Notices - Prop 65 Notice Sales Drawings - sa207485-01

Application

Substation

General

Connector Type	Terminal
Installation Torque	480
Recommended in-lb	
Material	Copper Alloy
Material - Hardware	DURIUM™ Silicon Bronze
One Wrench Installation	Υ
Physical Attribute - Pad	3 x 3 - 4 holes
Configuration	
Physical Attribute - Pad	Offset
Orientation	
Plated	Ν
Plating Type	Unplated
UPC	781810232217
UPC 12 Digit	7818102322177
Dimensione	
Dimensions	

Dimension - B Length inch	2.62 in
Dimension - D inch	3.00 in
Dimension - Hole Size fraction	9/16
Dimension - L Length Overall mm	149 mm
Dimension - Length Overall inch	5.87 in
Dimension - N inch	0.62 in
Dimension - Pad Width inch	3.00 in
Dimension - Width inch	4.88 in
Dimension - Width mm	124 mm
Physical Attribute - Tongue Angle	Straight