

# N2AH4444NHQ, Substation -Copper Terminal

By Burndy Catalog # N2AH4444NHQ

Substation Connectors.



# **Conductor Related**

Substation		Conductor - Connection Combination	Cable to Flat
General		Conductor - Copper Solid Size	4/0 AWG
Catalog Number Connector Type Installation Torque	N2AH4444NHQ Terminal 480	Conductor - Copper Solid Size Range Conductor - Copper Str Size	4/0 AWG 4/0 AWG;250 kcmil;300
Recommended in-lb Material Material - Hardware One Wrench Installation	Copper Alloy DURIUM™ Silicon Bronze Y		kcmil;350 kcmil;400 kcmil;450 kcmil;500 kcmil;550 kcmil;600 kcmil;700 kcmil;750 kcmil;800 kcmil;850 kcmil;900 kcmil;1000 kcmil
Physical Attribute - Pad Configuration Physical Attribute - Pad Orientation	4 x 4 - 4 holes Offset	Conductor - Copper Str Size Range Number of Conductors	4/0 AWG-1000 kcmil 2
Plated Plating Type	N Unplated	Certifications And Compliance	
UPC UPC 12 Digit	781810446744 7818104467444	Certification - CSA Approved Certification - ETL	No No
Dimensions		Certification - UL Recognized Certification - cULus	No No
Dimension - B Length inch Dimension - D inch Dimension - Hole Size fraction	2.88 in 4.00 in 9/16	Standards - RoHS Compliance Status UL Listed	EX
Dimension - L Length Overall	183 mm	Logistics	

## **Product Assets**


Minimum Pack Quantity

3D Models - N2AH4444NHQ\_MODEL-PDF 3D Models - N2AH4444NHQ\_MODEL-STEP 3D Models - N2AH4444NHQ\_MODEL-IGES Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog Catalogs - BURNDY Master Catalog - Section L - Bolted Substation Customer Notices - Prop 65 Notice Interactive Catalog - BURNDY Full-Line Digital Catalog Sales Drawings - 10069782

12

## Application

Dimension - B Length inch	2.88 in
Dimension - D inch	4.00 in
Dimension - Hole Size fraction	9/16
Dimension - L Length Overall	183 mm
mm	
Dimension - Length Overall	7.20 in
inch	
Dimension - N inch	1.12 in
Dimension - Pad Width inch	4.00 in
Dimension - Width inch	6.12 in
Dimension - Width mm	155 mm
Physical Attribute - Tongue	Straight
Angle	



©2024 Hubbell Incorporated. All rights reserved BRDY-N2AH4444NHQ-SPEC-EN | REV 8/2024