

NA14A2N, Substation - Aluminum **Bolted Terminal**

By Burndy Catalog # NA14A2N

Substation Connectors.



Substation

General

Catalog Number NA14A2N Body and Cap Clamping Element Design Connector Type Terminal 300 LBS/in Installation Torque

Recommended in-lb

Material Aluminum Alloy Material - Hardware Aluminum

One Wrench Installation Physical Attribute - Number of 2

Holes

Physical Attribute - Pad Offset

Alignment

Physical Attribute - Pad 1.62 x 3 - 2 holes

Configuration

Physical Attribute - Pad Straight

Orientation

Plated Ν

Unplated Plating Type **UPC** 781810078624 UPC 12 Digit 7818100786244

Dimensions

Dimension - B Length fraction 3-1/4 in Dimension - B Length inch 3.25 in Dimension - D inch 3.00 in Dimension - F Width Center to 1.75 in Center inch

Dimension - G inch 1.41 in Dimension - Height inch 3.12 in Dimension - Height mm 79.2 mm 9/16 Dimension - Hole Size fraction Dimension - L Length Overall 165 mm

mm



Dimension - Length Overall	6.50 in
inch	
Dimension - N inch	0.63 in
Dimension - Pad Width inch	1.62 in
Dimension - Width inch	2.80 in
Dimension - Width mm	71 mm

Conductor Related

Conductor - AL Tube Std Size 3/4 IPS Conductor - AL Tube Std Size 3/4 IPS Range Conductor - Connection Tube to Flat Combination Conductor - Copper Tube Std 3/4 IPS IPS Conductor - Copper Tube Std 3/4 IPS IPS Size Range Conductor Type • AL Tube Std-Size • CU Tube Std-Size

Certifications And Compliance

Number of Conductors

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance	CM
Status	
UL Listed	No

Logistics

Minimum Pack Quantity

Product Assets

Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog Interactive Catalog - BURNDY Full-Line Digital Catalog Sales Drawings - SA038849-01 Specifications - NA14A2N

