

Substation - Aluminum Bolted Terminal

By Burndy Catalog # NA18A4NQ

Substation Connectors.



Application

Substation

General

Clamping Element Design Body and Cap Connector Type **Terminal** Installation Torque 480 LBS/in Recommended in-lb

Material Aluminum Alloy Material - Hardware Aluminum

One Wrench Installation Physical Attribute - Number of 4

Holes

Physical Attribute - Pad Offset

Alignment

Physical Attribute - Pad 3.12 x 3 - 4 holes

Configuration

Physical Attribute - Pad Straight

Orientation

Plated

Plating Type Unplated UPC 781810119341 UPC 12 Digit 7818101193411

Dimensions

Dimension - B Length inch 4.25 in Dimension - D inch 3.00 in Dimension - F Width Center to 1.75 in Center inch Dimension - G inch 2.05 in Dimension - Height inch 4.47 in Dimension - Hole Size fraction 9/16 Dimension - L Length Overall 191 mm mm Dimension - Length Overall 7.50 in inch 0.63 in Dimension - N inch Dimension - Pad Width inch 3.12 in Dimension - Width inch 4.50 in Dimension - Width mm 114 mm

Conductor Related

Conductor - AL Tube Std Size 2 IPS Conductor - AL Tube Std Size 2 IPS Range

Conductor - Connection Tube to Flat Combination

Conductor - Copper Tube Std 2 IPS IPS

Conductor - Copper Tube Std 2 IPS IPS

Size Range

Conductor Type • AL Tube Std-Size

• CU Tube Std-Size

Number of Conductors

Certifications And Compliance

Certification - CSA Approved Certification - ETL Certification - UL Recognized Nο Certification - cULus No Standards - RoHS Compliance EX Status **UL** Listed No

Logistics

Minimum Pack Quantity

Product Assets

Catalogs - Full Line BURNDY Catalog Customer Notices - Prop 65 Notice Sales Drawings - SA038849-01

