

NA19A4N, Substation - Aluminum Bolted Terminal, 2-1/2" Al Pipe, 4-Hole

By Burndy
 Catalog # [NA19A4N](#)



Aluminium Bolted Terminal, Tube to Flat, 2 1/2" Al Pipe, 4 Pad Holes, 230 kV.

Features

- Type NA-A Aluminum Terminals for Tube to Pad
- Properly proportioned to minimize conductor corrosion due to galvanic action
- When properly used, this item does not require use of bimetallic plates, contact Burndy Technical Support for recommendations
- One-wrench installation

Application

Substation

General

Catalog Number	NA19A4N
Clamping Element Design	Body and Cap
Connector Type	Terminal
Installation Torque	480 LBS/in
Recommended in-lb	
Material	Aluminum Alloy
Material - Hardware	Aluminum
One Wrench Installation	Y
Physical Attribute - Number of Holes	4
Physical Attribute - Pad Alignment	Offset
Physical Attribute - Pad Configuration	3.75 x 3 - 4 holes
Physical Attribute - Pad Orientation	Straight
Plated	N
Plating Type	Unplated
UPC	781810003770
UPC 12 Digit	7818100037700

Dimensions

Dimension - B Length fraction	4-1/2 in
Dimension - B Length inch	4.50 in
Dimension - D inch	3.00 in
Dimension - F Width Center to Center inch	1.75 in
Dimension - G inch	2.19 in

Dimension - Height fraction	5
Dimension - Height inch	4.97 in
Dimension - Height mm	126.2 mm
Dimension - Hole Size fraction	9/16
Dimension - L Length Overall mm	197 mm
Dimension - Length Overall inch	7.75 in
Dimension - N inch	0.63 in
Dimension - Pad Width inch	3.75 in
Dimension - Width fraction	5 in
Dimension - Width inch	5.00 in
Dimension - Width mm	127 mm

Conductor Related

Conductor - AL Tube Std Size	2 1/2 IPS
Conductor - AL Tube Std Size Range	2 1/2 IPS
Conductor - Connection Combination	Tube to Flat
Conductor - Copper Tube Std Size	2 1/2 IPS IPS
Conductor - Copper Tube Std Size Range	2 1/2 IPS IPS
Conductor Type	<ul style="list-style-type: none"> • AL Tube Std-Size • CU Tube Std-Size
Number of Conductors	1

Certifications And Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Minimum Pack Quantity	2
-----------------------	---

Product Assets

Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog
Catalogs - BURNDY Master Catalog - Section L - Bolted
Substation
Interactive Catalog - BURNDY Full-Line Digital Catalog

Product Cross Section Image(s) - BUR_NA4N_LineArt
Sales Drawings - SA038849-01
Specifications - NA19A4N



A Hubbell brand

©2025 Hubbell Incorporated. All rights reserved
BRDY-NA19A4N-SPEC-EN | REV 1/2025