

Substation - Aluminum Bolted Terminal

By Burndy Catalog # NA20A34N

Substation Connectors.



Application

Substation

General

Clamping Element Design Body and Cap Connector Type **Terminal** Installation Torque 480 LBS/in

Recommended in-lb

Material Aluminum Alloy Material - Hardware Aluminum

One Wrench Installation Physical Attribute - Number of 4

Holes

Physical Attribute - Pad Offset

Alignment

Physical Attribute - Pad

Configuration

Physical Attribute - Pad Straight

3 x 3 - 4 holes

Orientation

Plated

Plating Type Unplated UPC 781810110911 UPC 12 Digit 7818101109111

Dimensions

Dimension - B Length inch 5.00 in Dimension - D inch 3.00 in Dimension - F Width Center to 1.75 in Center inch Dimension - G inch 2.43 in Dimension - Height inch 5.47 in Dimension - Hole Size fraction 9/16 Dimension - L Length Overall 211 mm mm Dimension - Length Overall 8.31 in inch 0.62 in Dimension - N inch Dimension - Pad Width inch 3.00 in Dimension - Width inch 5.63 in Dimension - Width mm 143 mm

Conductor Related

Conductor - AL Tube Std Size 3 IPS Conductor - AL Tube Std Size 3 IPS

Range

Conductor - Connection

Combination

Conductor - Copper Tube Std

Conductor - Copper Tube Std

Size Range

Conductor Type

• AL Tube Std-Size

Tube to Flat

3 IPS IPS

3 IPS IPS

• CU Tube Std-Size

Number Of Conductors

Certifications and Compliance

Certification - CSA Approved Standards - RoHS Compliance EX

Status

Logistics

Minimum Pack Quantity 2

Product Assets

Customer Notices - Prop 65 Notice Sales Drawings - SA038849-01

