

NA20A44N, Substation - Aluminum Bolted Terminal

By Burndy Catalog # NA20A44N

Substation Connectors.



Substation

General

Catalog Number NA20A44N
Clamping Element Design Body and Cap
Connector Type Terminal
Installation Torque 480 LBS/in

Recommended in-lb

Material Aluminum Alloy Material - Hardware Aluminum

One Wrench Installation Y
Physical Attribute - Number of 4

Holes

Physical Attribute - Pad Offset

Alignment

Physical Attribute - Pad 4 x 4.25 - 4 holes

Configuration

Physical Attribute - Pad Straight

Orientation

Plated N

 Plating Type
 Unplated

 UPC
 781810111017

 UPC 12 Digit
 7818101110177

Dimensions

Dimension - B Length inch 5.00 in
Dimension - D inch 4.25 in
Dimension - F Width Center to 1.75 in

Center inch

Dimension - G inch

Dimension - Height inch

Dimension - Height mm

Dimension - Hole Size fraction

Dimension - L Length Overall

2.43 in

5.47 in

38.9 mm

9/16

217 mm

mm

Dimension - Length Overall

inch

Dimension - N inch 1.12 in

8.56 in



Dimension - Pad Width inch	4.00 in
Dimension - Width inch	5.62 in
Dimension - Width mm	143 mm

Conductor Related

Conductor - AL Tube Std Size 3 IPS Conductor - AL Tube Std Size 3 IPS

Range

Conductor - Connection Tube to Flat

Combination

Conductor - Copper Tube Std 3 IPS IPS

Size

Conductor - Copper Tube Std 3 IPS IPS

Size Range

Conductor Type • AL Tube Std-Size

CU Tube Std-Size

Number of Conductors 1

Certifications And Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance	EX
Status	
UL Listed	No

Logistics

Minimum Pack Quantity

Product Assets

3D Models - NA20A44N_MODEL-STEP 3D Models - NA20A44N_MODEL-IGES 3D Models - NA20A44N_MODEL-PDF

Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog

Customer Notices - Prop 65 Notice

Interactive Catalog - BURNDY Full-Line Digital Catalog

Sales Drawings - SA038849-01 Specifications - NA20A44N

