

# NA20A4N, Substation - Aluminum Bolted Terminal, 3" Al Pipe, 4-Hole

By Burndy Catalog # NA20A4N

Aluminium Bolted Terminal, Tube to Flat, 3" Al Pipe, 4 Pad Holes, 230 kV.

## Application

Substation

#### General

Catalog Number	NA20A4N
Clamping Element Design	Body and Cap
Connector Type	Terminal
Installation Torque	480 LBS/in
Recommended in-lb	
Material	Aluminum Alloy
Material - Hardware	Aluminum
One Wrench Installation	Y
Physical Attribute - Number of	4
Holes	
Physical Attribute - Pad	Offset
Alignment	
Physical Attribute - Pad	4.38 x 3 - 4 holes
Configuration	
Physical Attribute - Pad	Straight
Orientation	
Plated	Ν
Plating Type	Unplated
UPC	781810003787
UPC 12 Digit	7818100037877

### Dimensions

Dimension - B Length fraction	5 in
Dimension - B Length inch	5.00 in
Dimension - D inch	3.00 in
Dimension - F Width Center to	1.75 in
Center inch	
Dimension - G inch	2.43 in
Dimension - Height fraction	5-1/2
Dimension - Height inch	5.47 in
Dimension - Height mm	138.9 mm
Dimension - Hole Size fraction	9/16
Dimension - L Length Overall	211 mm
mm	
Dimension - Length Overall	8.31 in
inch	
Dimension - N inch	0.62 in



Dimension - Pad Width inch	4.38 in
Dimension - Width fraction	5-5/8 in
Dimension - Width inch	5.62 in
Dimension - Width mm	143 mm

### **Conductor Related**

3 IPS
3 IPS
Tube to Flat
3 IPS IPS
3 IPS IPS
AL Tube Std-Size
CU Tube Std-Size
1

## **Certifications And Compliance**

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance	СМ
Status	
UL Listed	No

### Logistics

Minimum Pack Quantity 1

### **Product Assets**

Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog Catalogs - BURNDY Master Catalog - Section L - Bolted Substation Customer Notices - Prop 65 Notice Interactive Catalog - BURNDY Full-Line Digital Catalog Product Cross Section Image(s) - BUR\_NA4N\_LineArt Sales Drawings - SA038849-01 Specifications - NA20A4N



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved BRDY-NA20A4N-SPEC-EN | REV 10/2024