

Substation - Aluminum Bolted T Connector

By Burndy Catalog # NNT15A15A

Cast Al Alloy T Connector, 6.81 IN L, 3.06 IN W, Tube to Tube, 1 IN IPS Al (Run), 1 IN IPS Al (Tap), 1/2 IN-13 Bolt Size Dia.

Application

Substation

General

Catalog Number	NNT15A15A
Connector Type	T-Connector
Installation Torque	300 LBS/in
Recommended in-lb	
Material	Aluminum Alloy
Material - Hardware	Aluminum
One Wrench Installation	Υ
Physical Attribute - Number of	1
Run Conductors	
Physical Attribute - Number of	1
Tap Conductors	
Physical Attribute - Pad	90 Degree
Orientation	
Plated	Ν
Plating Type	Unplated
Туре	Bolted Tees
UPC	781810003916
UPC 12 Digit	7818100039166

Dimensions

Dimension - B Length fraction	3-1/2 in
Dimension - B Length inch	3.50 in
Dimension - Height fraction	3-3/8 in
Dimension - Height inch	3.38 in
Dimension - L Length Overall	173 mm
mm	
Dimension - Length BB inch	3.50 in
Dimension - Length Overall	6.81 in
inch	
Dimension - Width inch	3.06 in
Dimension - Width mm	78 mm



Conductor Related

Conductor - AL Tube Std Run	1 IPS
Conductor - AL Tube Std Run	1 IPS
Range	
Conductor - AL Tube Std Tap	1 IPS
Conductor - AL Tube Std Tap	1 IPS
Range	
Conductor - Connection	Tube to Tube
Combination	
Conductor Type	• AL Tube Std-Run
	 AL Tube Std-Tap

Certifications And Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance	СМ
Status	
UL Listed	No

Logistics

Minimum Pack Quantity 8

Product Assets

Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog Catalogs - BURNDY Master Catalog - Section L - Bolted Substation Customer Notices - Prop 65 Notice Interactive Catalog - BURNDY Full-Line Digital Catalog Product Cross Section Image(s) - BUR_FNNT_LineArt Sales Drawings - sc064838

