

Substation - Aluminum Bolted T Connector

By Burndy
Catalog # [NNT22A18A](#)



Substation Connectors.

Features

- Type NNT Aluminum T-Connectors for Aluminum and Copper Tube to Tube
- Properly proportioned to permit use on copper-aluminum conductor combinations
- Captured hex head bolts permit one-wrench installation

Application

Substation

General

Catalog Number	NNT22A18A
Connector Type	T-Connector
Installation Torque	480 LBS/in
Recommended in-lb	
Material	Aluminum Alloy
Material - Hardware	Aluminum
One Wrench Installation	Y
Physical Attribute - Number of Run Conductors	1
Physical Attribute - Number of Tap Conductors	1
Physical Attribute - Pad Orientation	90 Degree
Plated	N
Plating Type	Unplated
Type	Bolted Tees
UPC	781810095140
UPC 12 Digit	7818100951400

Dimensions

Dimension - B Length inch	6.00 in
Dimension - Height inch	6.19 in
Dimension - Height mm	157.2 mm
Dimension - L Length Overall mm	276 mm

Dimension - Length BB inch	4.25 in
Dimension - Length Overall inch	10.88 in
Dimension - Width inch	4.50 in
Dimension - Width mm	114 mm

Conductor Related

Conductor - AL Tube Std Run Range	4 IPS
Conductor - AL Tube Std Tap Range	2 IPS
Conductor - Connection Combination	Tube to Tube
Conductor Type	<ul style="list-style-type: none"> • AL Tube Std-Run • AL Tube Std-Tap

Certifications And Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	EX
UL Listed	No

Logistics

Minimum Pack Quantity	1
-----------------------	---

Product Assets

- [Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
- [Customer Notices - Prop 65 Notice](#)
- [Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
- [Sales Drawings - sc064838](#)
- [Specifications - NNT22A18A](#)