

Substation - Copper Coupler - Straight

By Burndy Catalog # NS1515

Cast Cu Alloy Bolted Coupler,1" IPS, Silicon Bronze H/W.



Application

Substation

General

Catalog Number NS1515
Connector Type Couplers
Installation Torque 240 LBS/in

Recommended in-lb

Material Copper Alloy, Cast Material - Hardware Silicon Bronze

One Wrench Installation Y
Physical Attribute - Number of 1

Run Conductors

Physical Attribute - Number of 1

Tap Conductors

Physical Attribute - Pad Straight

Orientation

Plated

Plating Type Unplated

Type Tube to Tube Couplers

UPC 781810002537 UPC 12 Digit 7818100025377

Dimensions

Dimension - B Length inch

Dimension - Height inch

Dimension - Height mm

Dimension - L Length Overall

2.13 in

54.1 mm

108 mm

mm

Dimension - Length BB inch 2.13 in
Dimension - Length Overall 4.25 in

inch

Dimension - Width inch 2.75 in
Dimension - Width mm 70 mm

Conductor Related

Conductor - Connection

Combination

Conductor - Copper Tube Std 1 IPS

Run

Conductor - Copper Tube Std 1 IPS

Size

Conductor - Copper Tube Std 1 IPS

Size Range

Conductor - Copper Tube Std 1 IPS

Tap

Certifications And Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance	EX
Status	
UL Listed	No

Logistics

Minimum Pack Quantity 2

Product Assets

Conductor Type

Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog Catalogs - BURNDY Master Catalog - Section L - Bolted

CU Tube Std-Size

Substation

Customer Notices - Prop 65 Notice

Interactive Catalog - BURNDY Full-Line Digital Catalog

Product Cross Section Image(s) - BUR_NS_LineArt

Sales Drawings - sa011052-01 Specifications - NS1515

