

Substation - Copper Coupler -Straight

By Burndy Catalog # NS1515HCHQ

Cast Cu Alloy Bolted Coupler,1" IPS, Silicon Bronze H/W.

Application

Substation

General

Catalog Number	NS1515HCHQ	Size
Connector Type	Couplers	Conductor - Copper Tube S
Installation Torque	480 LBS/in	Size Range
Recommended in-lb		Conductor - Copper Tube S
Material	Copper Alloy, Cast	Тар
Material - Hardware	Silicon Bronze	Conductor Type
One Wrench Installation	Y	
Physical Attribute - Number of	1	Certifications And Comp
Run Conductors		Certification - CSA Approve
Physical Attribute - Number of	1	Certification - ETL
Tap Conductors		Certification - UL Recognize
Physical Attribute - Pad	Straight	Certification - cULus
Orientation		Standards - RoHS Complian
Plated	Ν	Status
Plating Type	Unplated	UL Listed
Туре	Tube to Tube Couplers	
UPC	781810462577	Logistics
UPC 12 Digit	7818104625777	
		Minimum Pack Quantity
Dimensions		

Dimensions

Dimension - B Length inch 2.69 in Dimension - Height inch 2.57 in Dimension - Height mm 59.9 mm Dimension - L Length Overall 143 mm mm Dimension - Length BB inch 2.69 in Dimension - Length Overall 5.63 in inch Dimension - Width inch 3.22 in Dimension - Width mm 82 mm

Conductor Related



Conductor - Connection	Tube to Tube
Combination	
Conductor - Copper Tube Std	1 IPS
Run	
Conductor - Copper Tube Std	1 IPS
Size	
Conductor - Copper Tube Std	1 IPS
Size Range	
Conductor - Copper Tube Std	1 IPS
Тар	
Conductor Type	CU Tube Std-Size

pliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance	
Status	
UL Listed	No

1

Product Assets

3D Models - NS1515HCHQ_MODEL-STEP 3D Models - NS1515HCHQ_MODEL-IGES 3D Models - NS1515HCHQ_MODEL-PDF Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog Catalogs - BURNDY Master Catalog - Section L - Bolted Substation Customer Notices - Prop 65 Notice Interactive Catalog - BURNDY Full-Line Digital Catalog Sales Drawings - 10080987 Specifications - NS1515HCHQ

