

# **Substation - Copper Coupler - Straight**

By Burndy Catalog # NS1717HCHQ

Cast Cu Alloy Bolted Coupler,1.50" IPS, Silicon Bronze H/W.



# **Application**

Substation

# General

Catalog Number NS1717HCHQ
Connector Type Couplers
Installation Torque 480 LBS/in

Recommended in-lb

Material Copper Alloy, Cast Material - Hardware Silicon Bronze

One Wrench Installation Y
Physical Attribute - Number of 1

Run Conductors

Physical Attribute - Number of 1

Tap Conductors

Physical Attribute - Pad Straight

Orientation

Plated

Plating Type Unplated

Type Tube to Tube Couplers

UPC 781810462584 UPC 12 Digit 7818104625844

# **Dimensions**

Dimension - B Length inch

Dimension - Height inch

Dimension - Height mm

Dimension - L Length Overall

2.69 in

2.82 in

66.3 mm

mm

Dimension - Length BB inch 2.69 in
Dimension - Length Overall 5.75 in

inch

Dimension - Width inch 3.94 in
Dimension - Width mm 100 mm

#### **Conductor Related**

Conductor - Connection	Tube to Tube
Combination	
Conductor - Copper Tube Std	1 1/2 IPS
Run	
Conductor - Copper Tube Std	11/2 IPS
Size	
Conductor - Copper Tube Std	11/2 IPS
Size Range	
Conductor - Copper Tube Std	11/2 IPS
Тар	

CU Tube Std-Size

# **Certifications And Compliance**

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance	EX
Status	
UL Listed	No

#### Logistics

Conductor Type

Minimum Pack Quantity

# **Product Assets**

3D Models - NS1717HCHQ\_MODEL-IGES 3D Models - NS1717HCHQ\_MODEL-STEP 3D Models - NS1717HCHQ\_MODEL-PDF

Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog

Catalogs - BURNDY Master Catalog - Section L - Bolted

Substation

Customer Notices - Prop 65 Notice

Interactive Catalog - BURNDY Full-Line Digital Catalog

Sales Drawings - 10080987 Specifications - NS1717HCHQ

