

Substation - Copper T Connector -90 Degrees

By Burndy Catalog # NSNT1629

Cast Cu Alloy T Connector, Cu Tube to Cable, 1-1/4 IN IPS (Run), 6 AWG Sol. to 250 kcmil (Tap).



Application

Substation

General

Catalog Number NSNT1629 Connector Type T-Connector Installation Torque 240 LBS/in

Recommended in-lb

Material Copper Alloy, Cast Material - Hardware Silicon Bronze

One Wrench Installation Physical Attribute - Number of 1

Run Conductors

Physical Attribute - Number of 1

Tap Conductors

Plated Ν

Unplated Plating Type

Туре Tube to Cable Couplers

UPC 781810037140 UPC 12 Digit 7818100371400

Dimensions

Dimension - B Length inch 2.00 in Dimension - Height fraction 2-37/100 in Dimension - Height inch 2.37 in Dimension - Height mm 60.2 mm Dimension - L Length Overall 147 mm

Dimension - Length BB inch 2.38 in Dimension - Length Overall 5.78 in

inch

Dimension - Width fraction 1-24/25 in Dimension - Width inch 1.96 in Dimension - Width mm 50 mm

Conductor Related

Conductor - Connection Tube to Cable

Combination

Conductor - Copper Str Tap

Conductor - Copper Solid Tap

Conductor - Copper Solid Tap

Conductor - Copper Str Tap Range

Range

Conductor - Copper Tube Std

Conductor - Copper Tube Std

Run Range

Conductor Type

6 AWG;5 AWG;4 AWG;3

AWG;2 AWG;1 AWG 6 AWG-1 AWG

1/0 ;2/0 AWG;3/0 AWG;4/0

AWG;250 kcmil

1/0 AWG-250 kcmil

11/4 IPS

11/4 IPS

• CU C Str-Run

• CU C Solid-Run

• CU C Str-Tap

CU C Solid-Tap

• CU Tube Std-Run

Certifications And Compliance

Certification - CSA Approved Certification - ETL Certification - UL Recognized No Certification - cULus No Standards - RoHS Compliance EX Status

Logistics

UL Listed

Minimum Pack Quantity 3

Product Assets

Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog Catalogs - BURNDY Master Catalog - Section L - Bolted

No

Substation

Customer Notices - Prop 65 Notice

Interactive Catalog - BURNDY Full-Line Digital Catalog

Sales Drawings - se..087856-01

Specifications - NSNT1629

