



# PENE8, Oxide Inhibitor, 8 ounce

By Burndy  
Catalog # [PENE8](#)

Oxide Inhibiting Electrical Joint Compound, 8 OZ, For Cu-Cu,  
Cu Conduit Threads & Grounding Applications.



## Application

Copper to copper applications

## General

Application - For Use On	Copper to Copper
Container Type	Squeeze Bottle
EU RoHS Indicator	Yes
Pour Point	-40 °F
Sub Brand	PENETROX
Temperature - Dropping Point Fahrenheit	350 °F
Trade Name	PENETROX™
Type	Sealing compound
UPC	781810592854
UPC 12 Digit	7818105928544
Viscosity at 100 Fahrenheit	250 °F

## Certifications And Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	Yes

## Logistics

Carton Quantity	12
Container Size	8 oz
Minimum Pack Quantity	1
Pallet Quantity	2400

## Product Assets

- [3D Models - PENE8\\_MODEL-PDF](#)
- [3D Models - PENE8\\_MODEL-IGES](#)
- [3D Models - PENE8\\_MODEL-STEP](#)
- [Catalogs - Full Line BURNDY Catalog](#)
- [Product Cross Section Image\(s\) - BUR\\_PENE8\\_LineArt](#)
- [Sales Drawings - SC087710-01](#)
- [SDS - PENETROX E PORTUGUESE SDS \(GHS\) \(2020-01\)](#)
- [SDS - PENETROX E ESPANOL SDS \(GHS\) \(2020-01\)](#)
- [SDS - PENETROX E FRENCH SDS \(GHS\) \(2020-07\)](#)
- [SDS - PENETROX E RUSSIAN SDS \(GHS\) \(2020-07\)](#)
- [SDS - PENETROX E SDS \(GHS\) \(2020-01\)](#)
- [SDS - PENETROX E GERMAN SDS \(GHS\) \(2020-01\)](#)
- [SDS - PENETROX E Polish SDS \(GHS\) \(2020-07\)](#)



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.  
BRDY-PENE8-SPEC-EN | REV 5/2024