

# Q2A464N, Two Conductor Four Hole Mounting Heavy Duty Copper Lug Connector, 1100-1500 kcmil, 1/2" Stud, 1-3/4" Spacing, 2 Screws

By Burndy Catalog # Q2A464N

Copper Terminal, 4 Hole, 1100-1500 kcmil, 1/2" Stud, 1-3/4" Stud Hole Spacing, 2 Screws.

#### **Features**

- QIKLUG<sup>™</sup> Terminals feature compact size, high copper alloy terminal for joining cables to equipment pads or bars
- Each element accommodates a wide range of cable
- · One-wrench installation

#### General

Catalog Number Q2A464N
Connector Type Duel Clamp
Installation Torque 600 LBS/in

Recommended in-lb

Material Copper

Physical Attribute - Number of

Holes

Physical Attribute - Number of 2

Screws

Physical Attribute - Screw Type Hexagonal Bolt

Plated N
Plating Type Unplated
Temperature Rating 194
Trade Name QIKLUG™

Type Bolted Lugs & Terminals

UPC 781810322765 UPC 12 Digit 7818103227655

# **Dimensions**

Dimension - B Length inch

Dimension - Bolt Size fraction

Dimension - D inch

Dimension - F Width Center to

Center inch

2.00 in

1/2

3.25 in

2.31 in

Dimension - Height fraction 3-1/8 in
Dimension - Height inch 2.94 in
Dimension - Height mm 79.5 mm
Dimension - Hole Size fraction 9/16
Dimension - Hole Size inch 0.56 in
Dimension - Hole Size mm 14 mm
Dimension - L Length Overall 140 mm

mm



Dimension - Length Overall	5.50 in
inch	
Dimension - N inch	0.63 in
Dimension - Pad Width inch	3.50 in
Dimension - Stud Size inch	1/2
Dimension - Width inch	4.50 in
Dimension - Width mm	114 mm

#### **Electrical Ratings**

Rating - Minimum Voltage 600

### **Conductor Related**

Conductor - Copper Str Size 1250 kcmil;1300 kcmil;1500

cmil

Conductor - Copper Str Size 1250 kcmil-1500 kcmil

Range

Conductor Size 1100-1500 kcmil
Conductor Type CU C Str-Size

# **Certifications And Compliance**

Certification - CSA Approved No
Certification - ETL No
Certification - UL Listed Direct No
Burial
Certification - UL Recognized No
Certification - cULus No

Industry Standard(s) UL 486A-486B Standards - Industry Standards UL 486A-486B

Met

Standards - RoHS Compliance

Status

UL Listed Yes

# Logistics

Minimum Pack Quantity 1

#### **Product Assets**

Catalogs - BURNDY Master Catalog - Section A - Mechanical Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog

ΕX

Customer Notices - Prop 65 Notice Interactive Catalog - BURNDY Full-Line Digital Catalog Product Cross Section Image(s) - BUR\_Q2A284N\_LineArt Sales Drawings - sd023314-01 Specifications - Q2A464N



©2024 Hubbell Incorporated. All rights reserved BRDY-Q2A464N-SPEC-EN | REV 10/2024