

Q2A8C2, Two Conductor Two Hole Mounting Heavy Duty Copper Lug Connector, #14 Sol-#8 Str

By Burndy Catalog # Q2A8C2

Cast Cu Alloy QIKLUG, 2 Cables to Pads/Bars, #14 Sol. - #8 Str. Cu, 2 Pad Holes.



Features

- QIKLUG[™] Terminals feature compact size, high copper alloy terminal for joining cables to equipment pads or bars
- Each element accommodates a wide range of cable
- One-wrench installation

General

Connector Type Duel Clamp
Material Copper

Physical Attribute - Number of 2

Holes

Physical Attribute - Number of 2

Screws

Physical Attribute - Screw Hexagonal Bolt

Туре

Plated N

Plating Type Unplated
Temperature Rating 194
Trade Name QIKLUG™

Type Bolted Lugs & Terminals

UPC 781810176160 UPC 12 Digit 7818101761600

Dimensions

Dimension - Bolt Size fraction 1/2 Dimension - D inch Dimension - F Width Center to 0.88 in Center inch Dimension - Height fraction 1.00 in Dimension - Height inch Dimension - Hole Size inch 0.56 in Dimension - Hole Size mm 13 mm 60 mm Dimension - L Length Overall mm 2.38 in Dimension - Length Overall inch Dimension - N inch 0.5 inDimension - Pad Width inch 1.25 in Dimension - Width inch 1.69 in Dimension - Width mm 43 mm

Electrical Ratings

Rating - Minimum Voltage 600

Conductor Related

Conductor - Copper Solid Size 14 AWG;13 AWG;12 AWG;11

AWG;10 AWG;9 AWG;8 AWG

Conductor - Copper Solid Size 14 AWG-8 AWG

Range

Conductor - Copper Str Size 14 AWG;12 AWG;10 AWG;9

AWG;8 AWG 14 AWG-8 AWG

Conductor - Copper Str Size

Range

Conductor Size 14-8 AWG
Conductor Type CU C Str-Size

Certifications And Compliance

Certification - CSA Approved No
Certification - ETL No
Certification - UL Listed Direct No
Burial

Certification - UL Recognized No Certification - cULus No

Industry Standard(s) UL 486A-486B Standards - Industry UL 486A-486B

Standards Met

Standards - RoHS Compliance CM

Status

UL Listed Yes

Logistics

Minimum Pack Quantity 1

Product Assets

Catalogs - Full Line BURNDY Catalog Customer Notices - Prop 65 Notice Sales Drawings - sa005943-01



