

QQA262, Twin Clamping Two Hole Mounting Heavy Duty Copper Lug Connector



By Burndy Catalog # QQA262

Copper Terminal, Heavy Duty, 2 Hole, 1/0-2/0 AWG (Str), 3/8" Stud, 1" Stud Hole Spacing, 2 Screws.

Features

- QIKLUG[™] Terminals feature compact size, high copper alloy terminal for joining cables to equipment pads or bars
- Each element accommodates a wide range of cable
- One-wrench installation

Application

For Joining Copper Cable To Equipment Pads Or Bars

General

QQA262 Duel Clamp
Yes 180 LBS/in
Copper
2
2
Hexagonal Bolt
N
Unplated
MECHANICAL CONNECTOR,
QIKLUG
QIKLUG™
Bolted Lugs & Terminals
781810325858

Dimensions

Dimension - Bolt Size fraction 3/8 Dimension - D inch 1.94 in Dimension - F Width Center to 1.00 in Center inch Dimension - Height fraction 1.125 in Dimension - Height inch 1.13 in Dimension - Height mm 28.7 mm Dimension - Hole Size inch 0.41 in Dimension - Hole Size mm 10 mm Dimension - L Length Overall 106 mm mm

Dimension - Length Overall	4.19 in
inch	
Dimension - N inch	0.44 in
Dimension - Pad Width inch	0.81 in

Conductor Related

Conductor - Copper Str Navy	100 (61) Navy;125 (61) Navy
Size	
Conductor - Copper Str Navy	100 (61) Navy-125 (61) Navy
Size Range	
Conductor - Copper Str Size	1/0 ;2/0 AWG
Conductor - Copper Str Size	1/0 -2/0 AWG
Range	
Conductor Size	1/0-2/0 AWG
Conductor Type	CU C Str-Size
	 CU C Str Navy-Size

Certifications And Compliance

Buy American Compliant	Yes
Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL 486A-486B
Standards - Industry Standards	UL 486A-486B
Met	
Standards - RoHS Compliance	EX
Status	
UL Listed	Yes

Logistics

Minimum Pack Quantity 1

Product Assets

Catalogs - BURNDY Master Catalog - Section A - Mechanical Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog Interactive Catalog - BURNDY Full-Line Digital Catalog Product Cross Section Image(s) - BUR_QQA_LineArt Sales Drawings - SA..005911-01 Specifications - QQA262



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved BRDY-QQA262-SPEC-EN | REV 10/2024