

# **QR34**, Heavy Duty Copper Splice Reducer

By Burndy Catalog # QR34

Splice or Reducer, 400 - 500 kcmil, Recommended Tightening Torque: 375 IN-LB.



#### **Features**

- Type QR QIKLINK<sup>™</sup> splice or reducer features a neat, compact, easy to tape installation
- One-wrench installation

#### General

Catalog Number QR34
Connector Type In-Line
Installation Torque 375 LBS/in

Recommended in-lb

Material Copper Physical Attribute - Number of 2

Scrowic

Physical Attribute - Screw Type Hexagonal Bolt

Plated N

Plating Type Unplated
Trade Name QIKLINK™
UPC 781810334690

## **Dimensions**

Dimension - B Length fraction

Dimension - B Length inch

Dimension - Height fraction

Dimension - Height inch

Dimension - L Length Overall

1-3/8 in

1.38 in

2-1/16 in

2.06 in

mm

Dimension - Length Overall 3.06 in

inch

Dimension - Width fraction 1-7/16 in
Dimension - Width inch 1.44 in
Dimension - Width mm 37 mm

## **Conductor Related**

Conductor - Copper Str Size A 400 kcmil;450 kcmil;500 kcmil

Conductor - Copper Str Size A 400 kcmil-500 kcmil

Range

Conductor - Copper Str Size B 400 kcmil;450 kcmil;500 kcmil

Conductor - Copper Str Size B 400 kcmil-500 kcmil

Range

Conductor Size 400-500 kcmil

Conductor Type • CU C Str-Size A

• CU C Str-Size B

• CU C Solid-Size A

• CU C Solid-Size B

## **Certifications And Compliance**

Certification - CSA Approved No
Certification - ETL No
Certification - UL Recognized No
Certification - cULus No

Industry Standard(s) UL 486A-486B Standards - Industry Standards UL 486A-486B

Met

Standards - RoHS Compliance EX

Status

UL Listed Yes

#### Logistics

Minimum Pack Quantity 2

#### **Product Assets**

Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog

Catalogs - BURNDY Master Catalog - Section A - Mechanical

Customer Notices - Prop 65 Notice

Interactive Catalog - BURNDY Full-Line Digital Catalog

Product Cross Section Image(s) - BUR\_G4FQR\_LineArt

Sales Drawings - SA011559-01

Specifications - QR34

