

Substation - Aluminum Rigid Spacer

By Burndy
Catalog # [S2R486ACG1](#)



Rigid 13 IN Spacer, 2303.5 kcmil ASC, 230kV.

Application

Substation

General

| | |
|-------------------------|----------------------|
| Catalog Number | S2R486ACG1 |
| Clamping Element Design | 2 Piece Design |
| Connector Type | Spacer |
| Installation Torque | 480 in-lb |
| Recommended in-lb | |
| Material | Aluminum Alloy, Cast |
| One Wrench Installation | Y |
| Plated | N |
| Plating Type | Unplated |
| UPC | 621945257573 |
| UPC 12 Digit | 6219452575733 |

Dimensions

| | |
|---------------------------------|---------|
| Dimension - B Length inch | 2.00 in |
| Dimension - Height inch | 2.75 in |
| Dimension - Height mm | 0 mm |
| Dimension - L Length Overall mm | 216 mm |
| Dimension - Length Overall inch | 8.52 in |
| Dimension - Width inch | 2.00 in |
| Dimension - Width mm | 51 mm |

Conductor Related

| | |
|------------------------------------|--------------|
| Conductor - AL Str Size Range | 2303.5 kcmil |
| Conductor - Connection Combination | Cable Spacer |
| Number of Conductors | 2 |

Certifications And Compliance

| | |
|------------------------------------|----|
| Certification - CSA Approved | No |
| Certification - ETL | No |
| Certification - UL Recognized | No |
| Certification - cULus | No |
| Standards - RoHS Compliance Status | CM |
| UL Listed | No |

Logistics

| | |
|-----------------------|---|
| Minimum Pack Quantity | 2 |
|-----------------------|---|

Product Assets

- [3D Models - S2R486ACG1_MODEL-IGES](#)
- [3D Models - S2R486ACG1_MODEL-STEP](#)
- [3D Models - S2R486ACG1_MODEL-PDF](#)
- [Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
- [Customer Notices - Prop 65 Notice](#)
- [Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
- [Sales Drawings - CSD023113-01](#)
- [Specifications - S2R486ACG1](#)