

# SN18B, Nylon Splice For 22 - 18 AWG

By Burndy Catalog # SN18B

Nylon Splice For 22 - 18 AWG.

# Features

- Tin plated copper brazed butt seam
- Smooth funnel entry for easy wire insertion
- Mylon insulation offers high dielectric strength and stability

## Application

For Heavy Duty Application Requirements

## General

Catalog Number Color Code Connector Type EU RoHS Indicator Insulation Insulation Type Material Plated Plating Type	SN18B Red Brazed Seam Butt Splice Yes Y Nylon Copper Y Tin
Insulation	Y
Insulation Type	Nylon
Material	Copper
Plated	Y
Plating Type	Tin
Sub Brand	INSULINK
Trade Name	INSULINK™
Туре	SN
UPC	781810525104
UPC 12 Digit	7818105251044

## Dimensions

Dimension - L Length Overall	32 mm
mm	
Dimension - Length Overall	1.25 in
inch	
Dimension - Outside Diameter	0.12 in
inch	
Dimension - Strip Length inch	15/64 in

## **Electrical Ratings**

Voltage - Maximum

600 V

# In the second

## **Conductor Related**

Conductor - Copper Str Size	22 - 18 AWG
Range	
Conductor Size	22 - 18 AWG

## **Certifications And Compliance**

Buy American Compliant	Yes
Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL467
Standards - Industry Standards	UL467
Met	
Standards - RoHS Compliance	СМ
Status	
UL Listed	No

## Logistics

Carton Quantity	100
Minimum Pack Quantity	100

## **Product Assets**

3D Models - SN18B\_MODEL-STEP 3D Models - SN18B\_MODEL-IGES 3D Models - SN18B\_MODEL-PDF Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog Catalogs - BURNDY Master Catalog - Section B - Small Compression Interactive Catalog - BURNDY Full-Line Digital Catalog Product Cross Section Image(s) - BUR\_SN10\_LineArt Sales Drawings - 50094193 Specifications - SN18B



HUBBELL A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved BRDY-SN18B-SPEC-EN | REV 8/2024