

Uninsulated Locking Fork Terminal For 12 - 10 AWG

By Burndy Catalog # T106LF



Uninsulated Locking Fork Terminal For 12 - 10 AWG.

Features

- Locking Fork Tongue design
- Allows for fast installation, screw only has to be loosened for termination
- Internal configuration of the fork prevents the terminal from coming off the screw without applying a pulling force
- Locking fork is made from copper alloy, permits many installation while maintaining proper spring retention of forks

General

Connector Type	Locking Fork Terminal
Feature - Barrel Style	Shrouded
Material	Copper
Physical Attribute - Tongue Type	Fork
Plated	Υ
Plating Type	Unplated
Trade Name	HYLUG™
UPC	781810530726
UPC 12 Digit	7818105307266

Dimensions

Dimension - Bolt Size fraction	#4 - #6
Dimension - L Length Overall mm	23 mm
Dimension - Length Overall inch	0.90 in
Dimension - Pad Width inch	0.30 in
Dimension - Strip Length inch	11/32
Dimension - Stud Size inch	#4;#5;#6
Dimension - Z (inch)	0.29 in

Conductor Related

Conductor Size	12 - 10 AWG
Conductor Type	CU C Solid-Size
	CU C Str-Size

Certifications And Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	СМ
UL Listed	No

Logistics

Minimum Pack Quantity 100

Product Assets

Catalogs - Full Line BURNDY Catalog Sales Drawings - 50094175