

T1414, Uninsulated Ring Terminal For 16 - 14 AWG

By Burndy Catalog # T1414

Uninsulated Ring Terminal For 16 - 14 AWG.

Features

Long neck terminal permits easy bending and stacking of several terminals on a common stud

Application

For Control Wiring And Other Standard Duty Applications

General

Catalog Number Connector Type EU RoHS Indicator	T1414 Ring Terminal Yes
Feature - Barrel Type	Long
Material	Copper
Physical Attribute - Number of	1
Holes	
Physical Attribute - Tongue	Ring
Туре	
Plated	Υ
Plating Type	Tin
Sub Brand	HYLUG
Trade Name	HYLUG™
Туре	Ring Tongue
UPC	781810722480
UPC 12 Digit	7818107224800

Dimensions

Dimension - B Length fraction	13/50 in
Dimension - B Length inch	0.26 in
Dimension - Bolt Size fraction	1/4
Dimension - Diameter Max Size	0.08 in
inch	
Dimension - Hole Size fraction	17/63
Dimension - Hole Size inch	0.27 in
Dimension - L Length Overall	24
mm	
Dimension - Length Overall	0.95 in
inch	
Dimension - Pad Width inch	0.45 in
Dimension - Strip Length inch	9/32



Dimension - Stud Size inch1/4 inDimension - Z (inch)0.47 in

Conductor Related

Conductor Range#20 AWG to #14 AWGConductor Size16 - 14 AWGConductor Type• CU C Solid-Size• CU C Str-Size

Certifications And Compliance

Buy American Compliant Yes Certification - CSA Approved Yes Certification - ETL No Certification - UL Recognized No Certification - cULus No Industry Standard(s) UL467 Standards - Industry Standards UL486 Met Standards - RoHS Compliance СМ Status UL Listed Yes

Logistics

Carton Quantity	1200
Minimum Pack Quantity	100
Pallet Quantity	99999

Product Assets

3D Models - T1414_MODEL-PDF 3D Models - T1414_MODEL-STEP 3D Models - T1414_MODEL-IGES Catalogs - BURNDY Master Catalog - Section B - Small Compression Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog Customer Notices - Prop 65 Notice Interactive Catalog - BURNDY Full-Line Digital Catalog Product Cross Section Image(s) - BUR_K6FT_LineArt Sales Drawings - 50094154 Specifications - T1414

