

T148, Uninsulated Ring Terminal For 16 - 14 AWG

By Burndy Catalog # T148





Features

Long neck terminal permits easy bending and stacking of several terminals on a common stud

Application

For Control Wiring And Other Standard Duty Applications

General

Catalog Number T148

Connector Type Ring Terminal

EU RoHS Indicator Yes
Feature - Barrel Type Long
Material Copper

Physical Attribute - Number of

Holes

Physical Attribute - Tonque Ring

Туре

Plated Y
Plating Type Tin
Sub Brand HYLUG
Trade Name HYLUG™
Type Ring Tongue
UPC 781810722404
UPC 12 Digit 7818107224044

Dimensions

Dimension - B Length fraction 13/50 in
Dimension - B Length inch 0.26 in
Dimension - Bolt Size fraction #6 - #8
Dimension - Diameter Max Size 0.08 in

inch

Dimension - Hole Size fraction 1/6
Dimension - Hole Size inch 0.17 in
Dimension - L Length Overall 19

mm

Dimension - Length Overall 0.76 in

inch

Dimension - Pad Width inch

Dimension - Strip Length inch

Dimension - Stud Size inch

Dimension - Z (inch)

0.31 in

9/32 in

#6 - #8

0.35 in

Conductor Related

Conductor Range

Conductor Size 16 - 14 AWG
Conductor Type • CU C Solid-Size

• CU C Str-Size

#20 AWG to #14 AWG

Certifications And Compliance

Buy American Compliant Yes
Certification - CSA Approved Yes
Certification - ETL No
Certification - UL Recognized No
Certification - cULus No
Industry Standard(s) UL467
Standards - Industry Standards UL486

Met

Standards - RoHS Compliance CM

Status

UL Listed Yes

Logistics

Carton Quantity 1200
Minimum Pack Quantity 100
Pallet Quantity 99999

Product Assets

3D Models - T148_MODEL-STEP 3D Models - T148_MODEL-PDF 3D Models - T148 MODEL-IGES

Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog

Catalogs - BURNDY Master Catalog - Section B - Small

Compression

Customer Notices - Prop 65 Notice

Interactive Catalog - BURNDY Full-Line Digital Catalog Product Cross Section Image(s) - BUR_K6FT_LineArt

Sales Drawings - 50094154

Specifications - T148

